



Product Data Sheet

Clear & Satin Overlay Protective Foil

FORMULA / DESCRIPTION	1) OVC 003 TRANSPARENT 2) PIT 002 SATIN TRANSPARENT **SILICONE DIE ROLL ON**
CARRIER	- 19 μ (.00075") POLYESTER
CARD SUBSTRATES	- PVC / ABS
RELEASE TEMPERATURE	-- 130°C to 160°C DIE FACE
DWELL TIME	- 0.2 to 0.6 SECONDS
SIZE	- VARIOUS WIDTHS & LENGTHS AVAILABLE. - SLIT TO INDIVIDUAL PRINTER SPECIFICATIONS.
CHARACTERISTIC	1) HIGH GLOSS FINISH 2) SATIN FINISH - MEDIUM RELEASE. - CLEAN EDGE DEFINITION/ NO FILMINESS. - CLEAN EDGE DEFINITION/ NO FILMINESS. - EXCELLENT SCRATCH RESISTANCE. - EXCELLENT RESISTANCE TO SOLVENTS. - EXCELLENT RESISTANCE TO CHEMICALS.
MINIMUM ORDER QUANTITY	- NO MINIMUM QUANTITY.
SHELF LIFE/STORAGE	KEEP FOIL IN PROTECTIVE PACKAGE WHEN NOT IN USE. ALL DIAGENICS CARD SERVICES INC. PRODUCTS MAY BE SAFELY STORED FOR A PERIOD OF TWELVE (12) MONTHS AND MUST BE STORED IN ITS PROTECTIVE COVER IF SUPPLIED. FOILS MUST BE KEPT IN A CLEAN AREA, FREE FROM EXCESSIVE MOISTURE & SHOULD BE STORED AT 40 - 60% RELATIVE HUMIDITY, A WAY FROM ANY DIRECT HEAT SOURCE OR SUNLIGHT. AMBIENT TEMPERATURE SHOULD BE BELOW 38° C.

The information contained relates only to the specific identified substrate materials. This information should be used as a guide only in determining the product suitability for the application, and should be confirmed by independent test procedures before use.