



Product Data Sheet
Scratch-Off Hot Stamp
Foil High Opacity

FORMULA / DESCRIPTION	1) S0B221 - FINGERPRINT PATTERN - PIGMENTED 2) S0C290 - FINGERPRINT PATTERN - METALLIC 3) SOC294 - FINGERPRINT PATTERN - METALLIC WITH DISTRACTION COATING 4) SOC296 - PLAIN SILVER / GREY 5) SOC297 - SILVER SPLASH - DIFFRACTION 6) SOC298 - CHROME SPLASH - DIFFRACTION 7) SOQ303 - FINGERPRINT PATTERN - PIGMENTED
CARRIER	1) - 19µ (.00075") POLYESTER 2) thru 7) - 12µ (.0005") POLYESTER
CARD SUBSTRATES	- COATED PAPER- LAMINATED PAPER- PVC - ABS - HIPS
RELEASE TEMPERATURE	1) - 110°C - 135°C DIE FACE - METAL DIE 2) thru 6) - 100°C - 125°C DIE FACE - METAL DIE 7) - 75°C - 100°C DIE FACE - METAL DIE **ACTUAL DIE FACE TEMPERATURE**
SIZE	- VARIOUS WIDTHS & LENGTHS AVAILABLE - SLIT TO INDIVIDUAL PRINTER SPECIFICATIONS
CHARACTERISTIC	- EASY RELEASE - CLEAN EDGE DEFINITION - HIGH OPACITY - RESISTANT TO CLASS 2 LASER LIGHT SOURCE - EASY, CLEAN SCRATCH OFF REMOVAL WITH COIN OR FINGERNAIL
MINIMUM ORDER QUANTITY	- NO MINIMUM QUANTITY.
SHELF LIFE/STORAGE	KEEP FOIL IN PROTECTIVE PACKAGE WHEN NOT IN USE. ALL DIAGENICS CARD SERVICES INC. PRODUCTS MAY BE SAFELY STORED FOR A PERIOD OF TWELVE (12) MONTHS AND MUST BE STORED IN ITS PROTECTIVE COVER IF SUPPLIED. FOILS MUST BE KEPT IN A CLEAN AREA, FREE FROM EXCESSIVE MOISTURE & SHOULD BE STORED AT 40 - 60% RELATIVE HUMIDITY, AWAY FROM ANY DIRECT HEAT SOURCE OR SUNLIGHT. AMBIENT TEMPERATURE SHOULD BE BELOW 38° C.

The information contained relates only to the specific identified substrate materials. This information should be used as a guide only in determining the product suitability for the application, and should be confirmed by independent test procedures before use.