



# Product Data Sheet

## Cleaning Tape

<b>FORMULA / DESCRIPTION</b>	1) CT40 PINK 2) CT02 CLEAR BLUE
<b>ADHESIVE</b>	ACRYLIC
<b>TAPE THICKNESS</b>	1) 63 $\mu$ (.0025") - COMBINED CARRIER & ADHESIVE 2) 38 $\mu$ (.0015") - COMBINED CARRIER & ADHESIVE
<b>SIZE</b>	ALL DIAGENICS CARD SERVICES INC. TAPES CAN BE SLIT TO INDIVIDUAL PRINTER SPECIFICATIONS; INCLUDING DATACARD, NBS, AND CIM. MULTIPLE WIDTHS & LENGTHS ARE AVAILABLE.
<b>CHARACTERISTIC</b>	- SELF WOUND. - CONSISTENT EASY UNWIND. - EXACT SLITTING AND TENSION ELIMINATES EXCESS ROLL EDGE ADHESIVE. - ADHESION TO STEEL 27N/100mm -PER ASTM3330 - LONGITUDINAL TENSILE STRENGTH 210N/100mm -PER ASTM3759 - ELONGATION AT BREAK 15% -PER ASTM3759 - ROLLS ARE FREE FROM PARTICULATE AND CONTAMINATION.
<b>MINIMUM ORDER QUANTITY</b>	- NO MINIMUM QUANTITY.
<b>SHELF LIFE/STORAGE</b>	ALL DIAGENICS CARD SERVICES INC. PRODUCTS MAY BE SAFELY STORED FOR A PERIOD OF TWELVE (12) MONTHS AND MUST BE STORED IN ITS PROTECTIVE COVER, IF SUPPLIED. TAPE MUST BE KEPT IN A CLEAN AREA, FREE FROM EXCESSIVE MOISTURE AND AWAY FROM DIRECT HEAT SOURCE OR SUNLIGHT. RECOMMENDED STORAGE CONDITIONS ARE 21 °C AND 40% - 60% HUMIDITY.

The information contained relates only to the specific identified substrate materials. This information should be used as a guide only in determining the product suitability for the application, and should be confirmed by independent test procedures before use.