



# Product Data Sheet

## Activation Label

<b>PRODUCT SERIES</b>	<b>LO-100</b>
<b>MATERIAL</b>	Micro Sphere Adhesive
<b>SIZE</b>	<ul style="list-style-type: none"> <li>- 0.6875" x 1.5" (17mm x 38mm) - R-439</li> <li>0.5714" x 1.5" (15mm x 38mm portrait) - S-372</li> <li>1.5" x 0.5714" (38mm x15mm landscape)- S-338</li> <li>0.3937" x 1.653543" (10mm x 42mm) - R-458</li> <li>0.375" x 1.5" (10mm x 38mm) - R-432</li> <li>0.375" x 2.5" (10mm x 63mm) - R-400</li> <li>0.375" x 2.5" - (Composite die, only one security option) S-350</li> <li>0.375" x 2.25" (10mm x 57mm) Composite die, only one security option - S-364</li> <li>0.3149" x 1.5" (8mm x 38mm) - R-419</li> <li>0.3149" x 1.5625" (8mm x 40mm) - R-442</li> <li>0.3149" x 1.5748" (8mm x 40mm) - R-420</li> <li>0.3149" x 1.6535" (8mm x 42mm) - R-446</li> <li>0.3149" x 2.25" (8mm x 57mm) - R-428</li> <li>0.251969" x 1.321429" (6mm x 33mm) - R-444</li> <li>0.25" x 1.5" (6mm x 38mm) - R-421</li> <li>0.25" x 1.25" (6mm x 32mm) Composite die, only one security option - S-245</li> <li>0.25" x 2.0" (6mm x 50mm) Composite die, only one security option - S-374</li> <li>0.23622" x 1.751654" (6mm x 45mm) - R-452</li> <li>0.2362" x 1.3214" (6mm x 34mm) - R-448</li> <li>0.2362" x 0.7874" (6mm x 20mm) Composite die, only one security option - R-438</li> <li>0.2187" x 1.2187" (6mm x 30mm) - R-457</li> <li>0.1875" x 1.1875" (5mm x 30mm) Composite die, only one security option - S-251</li> <li>0.1875" x 0.75" (5mm x 19mm) - R-407</li> </ul>
<b>CHARACTERISTIC</b>	0% residue on 30 mil PVC cards
<b>MINIMUM ORDER QUANTITY</b>	- NO MINIMUM QUANTITY.
<b>SHELF LIFE/STORAGE</b>	ALL DIAGENICS CARD SERVICES INC. LABEL PRODUCTS MAY BE SAFELY STORED FOR A PERIOD OF SIX (6) MONTHS AND MUST BE STORED IN ITS PROTECTIVE COVER, IF SUPPLIED. LABELS MUST BE KEPT IN A CLEAN AREA, FREE FROM EXCESSIVE MOISTURE & SHOULD BE STORED AT 40 - 60% RELATIVE HUMIDITY, AWAY FROM ANY DIRECT HEAT SOURCE OR SUNLIGHT. AMBIENT TEMPERATURE SHOULD BE BELOW 38°C.

The information contained relates only to the specific identified substrate materials. This information should be used as a guide only in determining the product suitability for the application, and should be confirmed by independent test procedures before use.